

QUALITY DATE: 20/06/2012
ORDER CODE REPLACES: 21/12/2010

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
ANTISOIL
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (± 15%) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE

EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE
FIRE RESISTANCE UK

LANO CLASSIFICATION
CLASSIFICATION BS7131

EN 13501-1
BS 4790

OPTIMA SB/FS
OPT

± 400 & 500
COLLECTION
1/10" CUT PILE

PIECE DYED

PA



WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 680
± 1.830

± 4,0
± 6,0
± 260.040
± 39,40
± 66,00

±
±

±

✓
✓
✓
✓
✓
✓
✓
ANTISTATIC
✓
✓

E9FCCAF6

24664
Z-156.601-1090 - PA 6.6 / 121 / FS

10/268
U3P3E1C0

✓

CL.23/32
Domestic Heavy / Commercial General



LC2 

Bfl-s1 